


50JA

Potentiometer with a conductive plastic resistive element

Nomenclature

- **S** means special mechanical specifications not applicable to our standard.
- **50** means approx. size of base housing in mm.
- **J** means joystick controller.
- **A** means type 1-,2-, or 3-dimensional coordinates is available and also means potentiometers are mounted outside housing case.
- **K** means square shape.
- **Y** means kind of mechanism:
- **X** means 1-dimensional coordinate. **Y** means 2-dimensional coordinate
- **Z** means 3-dimensional coordinate.
- **Available directions of lever operation**
- **Standard version:**
- **O** : Omni-directional 360° operating type.
- **Special version:**
- **I** : I figure (Y) directional operating type.
- **L** : L figure(+Y, +X only) directional operating type.
- **X** : Cross direction of X and Y operating type.
- **Q** : Square-directional 360° operating angle.
- **Z** : In addition to omni-directional 360° operation, this type is 3-dimensional coordinate operation by rotating knob in which a potentiometer is mounted on the body side of joystick, and this is standard version, and also can be incorporated inside the rotating knob(T type) on request.
- **R** : In addition to square-directional 360° operation, this type is 3-dimensional coordinate operation by rotating knob in which a potentiometer is mounted on the body side of joystick, and this is standard version, and also can be incorporated inside the rotating knob(U type) on request.
- **S** : Special operating directions other than the above-mentioned types.



S **50** **J** **A** **K** - **Y** **O** - **2** **0** **R2** **G** - **0000**

Number of potentiometers to be incorporated.

- 0...no potentiometer incorporated.
- 1...1 potentiometer incorporated.
- 2...2 potentiometers incorporated.
- 3...3 potentiometers incorporated.

Number of switches to be incorporated.

- 0...no switch incorporated.
- 1...1 switch incorporated.
- 2...2 switches incorporated.
- 3...3 switches incorporated.
- 4...4 switches incorporated.
- 5...5 switches incorporated.
- 6...6 and over 6 switches incorporated.
- 9...other switches to your special request.

With spring return device :

- R1** : with spring return device for 1-dimensional coordinate.
- R2** : with spring return device for 2-dimensional coordinate.
- R3** : with spring return device for 3-dimensional coordinate.

Mounting accessories :

- G** : with dust proof rubber cover.
- P** : with sub-panel for mounting.

Special part number :

In case we produce customized products, we add 4-digit branch number.



50JAK-YO-20
(Standard)
(2-dimensional coordinate type)



50JAK-ZZ-30
(3-dimensional coordinate type)

STANDARD SPECIFICATIONS

●Mechanical Performance

Controlling range of operating lever :

- 2-dimensional coordinate type : Omni-directionally approx. $\pm 30^\circ \sim \pm 35^\circ$, operation from center position.
- 3-dimensional coordinate type : Approx. 320° rotation by knob-operation in addition to the controlling range of 2-dimensional coordinate operation.
(in case of center-returning type with spring return device, the operating range is approx. $\pm 45^\circ \sim \pm 50^\circ$ from center position.)

Operating force : Without spring return device.

Standard : Approx. 0.5~0.8N (50~80gf.)
High torque type : Approx. 2~6N (200~600gf.)
With spring return device : (subject to directivity)
X, Y directions : Approx. 0.8~1.5N (80~150gf.)
Z direction : Approx. 20~85mN·m (200~850gf·cm.)

Operating temperature range : $-20^\circ\text{C} \sim +65^\circ\text{C}$

Vibration : 10~55Hz 98m/s²

Shock : 294m/s²

Life expectancy : Approx. 5,000,000 operations.

Mass : 2-dimensional coordinate type : Approx. 280g
3-dimensional coordinate type : Approx. 230g

●Electrical Performance

Potentiometers mounted : SFCP22E 10k $\Omega \pm 15\%$, 0.2W, independent linearity tolerance $\pm 3\%$ (conductive plastic resistive element).

For X and Y axes : Electrical rotating angle : Approx. 60°

For Z axis : Electrical rotating angle : Approx. 320°

With spring return device for Z axis : Electrical rotating angle approx. 90°

[All terminals can be fitted with the AMP110 series fasten receptacle (2.8 × 0.5mm) or equivalents.]

In case of 3-dimensional coordinate Z-axis potentiometer inside-knob incorporated type (T-type), the following potentiometer is used : SFCP12AC 10k $\Omega \pm 15\%$, independent linearity tolerance $\pm 3\%$, 0.06W (Electrical rotating angle : Approx. 90°)

Output smoothness : Below 0.2% against input voltage.


Contact resistance variation : Below 5% C.R.V.

Resolution : Essentially infinite

Dielectric strength : 1 minute at 500V.A.C.

Insulation resistance : Over 1,000M Ω at 500V.D.C.


●Terminal Connection Diagram




●Special Specifications Available

Please see page 45, a table of "Standard and Special Specifications Available".

Standard Dimensions



■Panel Arrangements



Note : In case of JC with dust proof rubber cover, the dimensions of "*" part changes to $\phi 44$ mm. hole.

- Note: 1) In case of JC with dust-proof rubber cover, the dimensions of dress panel and *part dimension shall be changed numbers in parentheses.
2) In case of type Q, R and U, the angle of mark "*" becomes 360° square-directional and $\pm 20^\circ \sim \pm 25^\circ$ from center position.
3) 4 pcs. of mounting screw (M3 × 14) are attached.

(Unit : mm)